



Angular contact spherical plain bearings GE80-SX (Series GE..-SX)

requiring maintenance, to DIN ISO 12 240-2

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system (<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	80 mm	Tolerance: 0 / -0,015
D	125 mm	Tolerance: 0 / -0,02
T	29 mm	Tolerance: +/-0,25
A	14,5 mm	
B	27 mm	Tolerance: 0 / -0,3
C	27 mm	Tolerance: 0 / -0,3
D ₁	90,5 mm	
d _a max	88 mm	
D _a min	99 mm	
d _b max	104 mm	
D _b min	117 mm	
d _k	115 mm	
r _{1s} min	1,5 mm	Chamfer dimension
r _{2s} min	0,6 mm	Chamfer dimension
s	10 mm	
α	2 °	
m	1,5 kg	Mass
C _r	245000 N	Basic dynamic load rating, radial
C _{0r}	1220000 N	Basic static load rating, radial

