



SB12V20P-FC

Lightweight Lithium Ion starter battery, 7.05 lb / 3.2 kg kilogram, specially developed for motorsport.

Safety

Super B batteries are based on Lithium Iron Phosphate technology (LiFePO4). This so called Lithium Ion technology as used in the super B batteries is the safest Lithium Ion technology today. On top of that our specially designed casing and electronics further increase safety and durability.

Use

Please take these advices into account while using the battery.

1. Do not jumpstart.
2. Use correct charger.
3. Make sure the battery does not get deeply discharged. If the battery has no charge remaining when you check it, consider it to be damaged. Do not attempt to recharge or use it.
4. This battery is specially developed for motorsport. If you want to use it on road, please consult Super B.

-  **Recharges much faster**
-  **Longer service life**
-  **Incredible small size**
-  **Weighs less**
-  **Low self discharge**

Applications for SB12V20P-FC

DTM	Group C	WRC
BTCC	WTCC	NASCAR
LMS	GT's	GT Endurance
Dakar Rally Raid	Britsports	ALMS

Technical specifications SB12V20P-FC

SKU/EAN13	8718531360051
Battery Designation	4IFP83/121/239-8
Height (mm)	237,50 / 238,50
Diameter (mm)	NA
Width (mm)	119,50 / 120,50
Thickness (mm)	81,50 / 82,50
Nominal voltage (V)	13,2V
Charge method	CCCV
End of charge voltage (V)	15,2V
End of charge voltage (V) for endurance (cycle life)	14,4V
Charge current (A)	80A (4C)
Charge current (A) for endurance (cycle life)	24A (1C)
End-of-discharge voltage (V)	8V
?End-of-discharge voltage (V) for endurance (cycle life)	10V
Discharge current (A)	560A (30C)
Discharge current (A) for endurance (cycle life)	18,4A (1C)
Discharge pulse current (A) (10 seconds)	960A (52C)
Discharge pulse current (A) (1 second)	1200A (65C)
Discharge performance at 20 °C (rated capacity)	18,4Ah / 242,88Wh
Discharge performance at -20 °C (capacity)	16,56Ah / 218,592Wh
High rate discharge performance at 20 °C (capacity)	17,48Ah / 230,736Wh
EqPb (Equals Lead acid battery)	70 to 100Ah
Operating temperature range	-30°C to +60°C



Be in charge. **Super B.**

Storage temperature range	-50°C to +60°C
Weight	3,2kg

Be in charge. **Super B**

Expolaan 50
7556 BE Hengelo
The Netherlands

T +31 (0)748200010
F +31 (0)74 8200011
E info@super-b.com