

TECHNICAL DATA SHEET

XTC 5W40

DESCRIPTION

High performance synthetic oil for petrol and diesel engines dated from 2000 and later. It is suitable for turbo-charged or not, multivalve and diesel direct injection engines.

APPLICATION

Bardahl XTC 5w40 can be used all year long and in the most difficult operating conditions. It is compatible with catalytic converters.

SPECIFICATIONS

This product offers the following performance level:

ACEA	A3 B4 -12
API	SN / CF
VW	502.00 / 505.00
MB	229.3 / 226.5
Porsche	A40
BMW	Longlife-01
GM	LL-B-025
PSA	B71 2296
Renault	RN0700 / RN0710
Fiat	9.55535-M2

PROPERTIES

- ✓ Offers a stable viscosity.
- ✓ Provides an excellent resistance against shearing.
- ✓ Makes cold starting easier.
- ✓ Offers a good resistance against oxidation.

TECHNICAL DATA SHEET

TECHNICAL DATA

Density at 15°C	Kg/l	0,853
Viscosity at -35°C	mPa.s	5410
Viscosity at 40°C	mm ² /s	88,40
Viscosity at 100°C	mm ² /s	14,60
Viscosity Index		173
Flash point COC, °C	°C	223
Pour point, °C	°C	-42
TBN alcalinity	mgKOH/g	10,5
Sulphated ash contents	%	1,33

RECOMMENDATIONS

Handling: any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36160	6 x 400 ML
36161	12 x 1 L
36163	3 x 5 L
36168	20 L
36164	60 L
36167	205 L